


## UKCA marking information – Colas Ltd

 0836	
<b>Colas Ltd, 6210 Bishops Court,  Birmingham Business Park  Solihull, Birmingham, B37 7YB</b>  <b>13</b>  C27 UK 0836-CPR-13/F035	
<b><i>BS EN 13808</i></b> <i>Cationic bituminous emulsion</i>  <b><i>RS Bitukold C60B3/4 C65B3/4</i></b> <i>intended to be used for surface treatment as joint sealing in road construction and  road maintenance</i>	
<b>EMULSION</b> <ul style="list-style-type: none"> <li>• Efflux 2 mm at 40°C - EN 12846-1</li> <li>• Water effect on binder adhesion – EN 13614</li> <li>• Breaking behaviour – EN 13075-1</li> </ul>	NR (Class 0) ≥ 90 (Class 3) 70-195 (Class 3/4)
<b>RECOVERED BINDER</b> <ul style="list-style-type: none"> <li>• Penetration at 25°C - EN 1426</li> <li>• Softening point – EN 1427</li> <li>• Cohesion by pendulum – EN 13588</li> </ul>	≤ 150 (Class 4) ≥ 39 (Class 7) NR
<b>STAGE 1 DURABILITY - STABILISED BINDER</b> <ul style="list-style-type: none"> <li>• Durability of penetration at 25°C – EN 1426</li> <li>• Durability of softening point – EN 1427</li> <li>• Durability of cohesion by pendulum – EN 13588</li> </ul>	NPD NPD NR
<b>STAGE 2 DURABILITY - AGED BINDER</b> <ul style="list-style-type: none"> <li>• Durability of penetration at 25°C – EN 1426</li> <li>• Durability of softening point – EN 1427</li> <li>• Durability of cohesion by pendulum – EN 13588</li> </ul>	NPD NPD NR
Dangerous regulated substances	NPD

**UK  
CA**

0836

**Colas Ltd, 6210 Bishops Court,  
Birmingham Business Park  
Solihull, Birmingham, B37 7YB**

**13**

C27 UK 0836-CPR-13/F035

***BS EN 13808***

*Cationic bituminous emulsion*

***RS Bitukold C60B3/4 C65B3/4***

*intended to be used for surface treatment as joint sealing in road construction and  
road maintenance*