



0836

**Colas Ltd, 6210 Bishops Court,
Birmingham Business Park
Solihull, Birmingham, B37 7YB**

13

C9/2 UK 0836-CPR-13/F035

BS EN 13808

Cationic bituminous emulsion

Cationic Slurry Seal - C55B(F) C60B(F)

*intended to be used for surface treatment as slurry systems
(slurry seals and micro surfacing)*

EMULSION

- Efflux 2 mm at 40°C 15-70 s Class 3
 - Water effect on binder adhesion – EN 13614 NR (Class 0)
 - Breaking behaviour – EN 13075-1 NPD

RECOVERED BINDER

- Penetration at 25°C ≤ 330 (Class 7)
 - Softening point – EN 1427 ≥ 35 (Class 8)
 - Cohesion by pendulum – EN 13588 NR

STAGE 1 DURABILITY - STABILISED BINDER

- Durability of penetration at 25°C – EN 1426 NPD
 - Durability of softening point – EN 1427 NPD
 - Durability of cohesion by pendulum – EN 13588 NR

STAGE 2 DURABILITY - AGED BINDER

- Durability of penetration at 25°C – EN 1426 ≤ 330 (Class 7)
 - Durability of softening point – EN 1427 ≥ 35 (Class 8)
 - Durability of cohesion by pendulum – EN 13588 NR

Dangerous regulated substances

NPD



0836

**Colas Ltd, 6210 Bishops Court,
Birmingham Business Park
Solihull, Birmingham, B37 7YB**

13

C9/2 UK 0836-CPR-13/F035

BS EN 13808
Cationic bituminous emulsion

Cationic Slurry Seal - C55B(F) C60B(F)
*intended to be used for surface treatment as slurry systems
(slurry seals and micro surfacing)*