


UKCA marking information – Colas Ltd

 0836	
Colas Ltd, 6210 Bishops Court, Birmingham Business Park Solihull, Birmingham, B37 7YB 13 C6 UK 0836-CPR-13/F035	
<i>BS EN 13808</i> <i>Cationic bituminous emulsion</i> <i>Prinmuls MP90X C70BPF2/3/4</i> <i>intended to be used for surface treatment as surface dressings</i>	
EMULSION <ul style="list-style-type: none"> • Efflux 4 mm at 40°C - EN 12846-1 • Water effect on binder adhesion – EN 13614 • Breaking behaviour – EN 13075-1 	5-100 s (Class 5/6) ≥ 90 (Class 3) ≤ 195 (Class 2/3/4)
RECOVERED BINDER <ul style="list-style-type: none"> • Penetration at 25°C - EN 1426 • Softening point – EN 1427 • Cohesion by pendulum – EN 13588 	≤ 220 (Class 5) ≥ 50°C (Class 4) ≥ 1.4 J/cm ² (Class 2)
STAGE 1 DURABILITY - STABILISED BINDER <ul style="list-style-type: none"> • Durability of penetration at 25°C – EN 1426 • Durability of softening point – EN 1427 • Durability of cohesion by pendulum – EN 13588 	NPD NPD NPD
STAGE 2 DURABILITY - AGED BINDER <ul style="list-style-type: none"> • Durability of penetration at 25°C – EN 1426 • Durability of softening point – EN 1427 • Durability of cohesion by pendulum – EN 13588 	≤ 150 (Class 4) NPD ≥ 1.4 J/cm ² (Class 2)
Dangerous regulated substances	NPD

**UK
CA**

0836

**Colas Ltd, 6210 Bishops Court,
Birmingham Business Park
Solihull, Birmingham, B37 7YB**

13

C6 UK 0836-CPR-13/F035

BS EN 13808

Cationic bituminous emulsion

Prinmuls MP90X C70BPF2/3/4

intended to be used for surface treatment as surface dressings