


UKCA marking information – Colas Ltd

 0836	
Colas Ltd, 6210 Bishops Court, Birmingham Business Park Solihull, Birmingham, B37 7YB 13 C29 UK 0836-CPR-13/F035	
<i>BS EN 13808</i> <i>Cationic bituminous emulsion</i> <i>Leochip VLS - C67B</i> <i>intended to be used for surface treatment as surface dressings</i>	
EMULSION	
• Dynamic viscosity at 40°C - EN 13302	Min. 8000 mPa.s (0.005s ⁻¹) or Max. 1200 mPa.s (1s ⁻¹)
• Water effect on binder adhesion – EN 13614	≥ 90 (Class 3)
• Breaking behaviour – EN 13075-1	NPD
RECOVERED BINDER	
• Penetration at 25°C	≤ 220 (Class 5)
• Softening point – EN 1427	≥ 35 (Class 8)
• Cohesion by pendulum – EN 13588	NR
STAGE 1 DURABILITY - STABILISED BINDER	
• Durability of penetration at 25°C – EN 1426	NPD
• Durability of softening point – EN 1427	NPD
• Durability of cohesion by pendulum – EN 13588	NR
STAGE 2 DURABILITY - AGED BINDER	
• Durability of penetration at 25°C – EN 1426	≤ 220 (Class 5)
• Durability of softening point – EN 1427	≥ 35 (Class 8)
• Durability of cohesion by pendulum – EN 13588	NR
Dangerous regulated substances	NPD

**UK
CA**

0836

**Colas Ltd, 6210 Bishops Court,
Birmingham Business Park
Solihull, Birmingham, B37 7YB**

13

C29 UK 0836-CPR-13/F035

BS EN 13808
Cationic bituminous emulsion

Leochip VLS - C67B
intended to be used for surface treatment as surface dressings