


## UKCA marking information – Colas Ltd

 0086	
<b>Colas Ltd, 6210 Bishops Court, Birmingham Business  Park, Solihull Parkway,  Birmingham B37 7YB</b>  <b>10</b>  M5 UK 0086-CPR-649099	
<b>BS EN 14023</b> <i>Polymer modified bitumen</i>  <b><i>H4 Polymer – 25/55-50</i></b> <i>intended to be used for sealing</i>	
<b>CONSISTENCY</b> <ul style="list-style-type: none"> <li>• Penetration at 25°C, 0,1 mm – EN 1426</li> <li>• Softening point, °C – EN 1427</li> </ul>	45-80 Class 4 ≥ 50 (Class 8)
<b>COHESION</b> <ul style="list-style-type: none"> <li>• Tensile test at 5°C [100 mm/min traction], J/cm<sup>2</sup> – EN 13587 &amp; EN 13703</li> </ul>	≥ 3 (Class 2)
<b>RESISTANCE TO HARDENING [EN 12607-1]</b> <ul style="list-style-type: none"> <li>• Retained penetration at 25°C, % – EN 1426</li> <li>• Increase in softening point, °C – EN 1427</li> <li>• Change of mass, % – EN 12607-1</li> </ul>	≥ 55 (Class 6) ≤ 12 (Class 4) ≤ 0.5 (Class 3)
<b>BRITTLENESS AT LOW SERVICE  TEMPERATURE</b> <ul style="list-style-type: none"> <li>• Fraass breaking point, °C – EN 12593</li> </ul>	≤ -20 (Class 9)
<b>STRAIN RECOVERY</b> <ul style="list-style-type: none"> <li>• Elastic recovery at 25°C, % – EN 13398</li> <li>• Elastic recovery at 10°C, % – EN 13398</li> </ul>	≥ 50 (Class 5) NPD
Dangerous regulated substances	NPD

**UK  
CA**

0086

**Colas Ltd, 6210 Bishops Court, Birmingham Business  
Park, Solihull Parkway,  
Birmingham B37 7YB**

**10**

M5 UK 0086-CPR-649099

**BS EN 14023**

*Polymer modified bitumen*

***H4 Polymer – 25/55-50***

*intended to be used for sealing*